

Thermal Conductive Heating and Steam-Enhanced Extraction

John LaChance
VP Hydrogeology
TerraTherm, Inc.

New England Waste Management Officials' Association

In-Situ Thermal Remediation Workshop

June 13, 2012 – *Quinebaug Valley Community College in Danielson, CT*
June 14, 2012 - *Westford Regency Inn and Conference Center in Westford, MA*


ISTR Technology Alphabet Soup

- ➡ • Steam-Enhanced Extraction (SEE)*
 - Electrical Resistance Heating (ERH)*
 - Electro-Thermal Dynamic Stripping Process (ET-DSP™)
- ➡ • In Situ Thermal Desorption (ISTD)*
 - Thermal Conduction Heating (TCH) + Vacuum Recovery
- ➡ • Combinations*: ISTD/SEE (ET-DSP™/SEE)
- Radio Frequency Heating


➡ Focus of Talk

*Offered by TerraTherm, Inc.


ISTD/TCH* - Heating governed by **thermal conductivity** ($f \sim 3$) nearly uniform



ERH/ET-DSP* - Heating governed by **electrical conductivity** ($f \sim 200$) may require stacked electrodes



SEE* - Heating governed by **hydraulic conductivity** non-uniform steam flow





***Offered by TerraTherm, Inc.**



NEWMOA Thermal Remediation Workshop 3

TerraTherm ISTD/TCH Heaters




Covered by one or more of the following: U.S. Patent Nos. 5,190,405, 5,318,116, 6,485,232 and 6,632,047. International patents (e.g., EPC 1272290).





ISTD+SEE in Complex Stratigraphy



NEWMOA Thermal Remediation Workshop

9



TCH	CVOC	BTEX	Chloro-benzenes	Gasoline	Diesel	Oils > 50 cp	Creosote, 10-100 cp	MGP coal tar, viscous		
Sand, vadose									Effective	
Sand, saturated									Promising/site specific	
Silt, vadose									Problematic/unproven	
Silt, saturated									Will not be effective	
Clay, vadose										
Clay, saturated										
Crystalline rock										
Cemented sedimentary rock										
Organic rock										



SEE	CVOC	BTEX	Chloro-benzenes	Gasoline	Diesel	Oils > 50 cp	Creosote, 10-100 cp	MGP coal tar, viscous		
Sand, vadose									Effective	
Sand, saturated									Promising/site specific	
Silt, vadose									Problematic/unproven	
Silt, saturated									Will not be effective	
Clay, vadose										
Clay, saturated										
Crystalline rock										
Cemented sedimentary rock										
Organic rock										

TCH+SEE	CVOC	BTEX	Chloro-benzenes	Gasoline	Diesel	Oils > 50 cp	Creosote, 10-100 cp	MGP coal tar, viscous		
Sand, vadose									Effective	
Sand, saturated									Promising/site specific	
Silt, vadose									Problematic/unproven	
Silt, saturated									Will not be effective	
Clay, vadose										
Clay, saturated										
Crystalline rock										
Cemented sedimentary rock										
Organic rock										


NEWMOA Thermal Remediation Workshop

10






ISTD - SEE Combination



NEWMOA Thermal Remediation Workshop

15

ISTD - SEE Combination – Result



NEWMOA Thermal Remediation Workshop

16

Data Needs

- Good Conceptual Model
 - Definition of treatment zone
 - Comprehensive list of COCs, concentrations, and mass estimates
 - Geology and Hydrogeology (stratigraphy, permeability, hydraulic gradients, gw flow velocities)
- Treatment Objectives
- Site Constraints

NEWMOA Thermal Remediation Workshop

17



**Remediation using ISTD and steam – source removal
and plume effects
Lindven, Denmark**

NEWMOA Thermal Remediation Workshop

18

Why stay and listen?

- DNAPL source zone “removed” – does it make a difference?
- How to use thermal in tight spaces under buildings
- Use of steam and conductive heating together – the site conditions should determine which method, not what the vendor says
- Thermal is cool!

NEWMOA Thermal Remediation Workshop

19


Why clean up?

Plume length >3,300 ft


Two municipal wells downgradient of site – supplying more than 100,000 citizens

Groundwater velocity ~160 ft/year

Remediation objective: Clean up source zone




Source zone location



NEWMOA Thermal Remediation Workshop

21


Contaminant distribution, geology and hydrogeology



NEWMOA Thermal Remediation Workshop

22


Thermal Concept (SEE and TCH)



NEWMOA Thermal Remediation Workshop

23


Thermal Concept (SEE and TCH)



NEWMOA Thermal Remediation Workshop

24


Thermal Concept (SEE and TCH)



NEWMOA Thermal Remediation Workshop

25

Thermal Concept (SEE and TCH)



NEWMOA Thermal Remediation Workshop

26



Drilling between dry cleaning machines, walls, cables and pipes

NEWMOA Thermal Remediation Workshop


27



Indoor heater installation

NEWMOA Thermal Remediation Workshop

28



Wells

NEWMOA Thermal Remediation Workshop


29



Treatment system in two levels due to limited space at site

NEWMOA Thermal Remediation Workshop

30



Hot Soil Sampling - Equipment

- Intact core samples are needed to minimize vaporization of CVOCs during sampling
- Samples typically collected using a core barrel-type sampler equipped with stainless steel or Teflon sleeves
- Lengths and diameter of sample tools may vary from driller to driller



Hot Soil Sampling - Sample Collection

- The core barrel sampler and sample sleeve are assembled and advanced to the desired depth
- Samples are collected
- Full recovery not always possible



- Standard drilling equipment utilized

Hot Soil Sampling - Sample Collection (Cont.)

- Once removed from the borehole, the core barrel is disassembled and the sample sleeve is removed
- The ends of the sample sleeve are immediately covered with Teflon tape and capped



Hot Soil Sampling - Sample Collection (Cont.)

- Samples are placed into an ice bath for cooling containing drains to allow melt water to freely drain
- Once cooled to a temperature no higher than 10°C (50°F) the sample is ready to be containerized





Hot Soil Sampling - Sample Collection (Cont.)




- Samples are sealed tightly in a plastic bag for shipment to the laboratory
- Laboratory will extrude the soil
- Alternatively, the cooled samples may be processed in the field
- Commercial systems like the En Core® sampler may also be utilized






Effect on plume?



Predicted PCE Plume - Without Source Removal

- expected to reach municipal wells



Predicted PCE Plume - With Source Removal

- mass flux significantly reduced
- natural degradation attenuates plume
- municipal drinking water wells protected



NEWMOA Thermal Remediation Workshop

41

Conclusion

- 4000 kg of DNAPL were removed – 10 kg left
- Mass discharge reduced by ~ 300-800 times
- Plume has started shrinking
- Long-term benefit predicted – no need to treat groundwater for drinking purposes



NEWMOA Thermal Remediation Workshop

42

Fractured Rock Site in Southeastern US

- Focused Cleanup of TCE Source Zone
 - DNAPL
 - Above and below the water table
 - Saprolite, weathered bedrock, and fractured bedrock
- Leave groundwater plume for MNA and/or Enhanced Bio
- November 2006 to July 2007
- Active Manufacturing Facility



NEWMOA Thermal Remediation Workshop

43


Fractured Rock Site - Plan View



NEWMOA Thermal Remediation Workshop

44


ISTD Wellfield



NEWMOA Thermal Remediation Workshop

45


Conceptual Cross-Section Through Treatment Zone



NEWMOA Thermal Remediation Workshop

46


ISTD Thermal Wells



NEWMOA Thermal Remediation Workshop

47


Starting Temperature Profile



NEWMOA Thermal Remediation Workshop

48


Temperature Profile at 4 Weeks



NEWMOA Thermal Remediation Workshop

49


Final Temperatures within Treatment Zone



NEWMOA Thermal Remediation Workshop

50


Mass Removal During ISTD Treatment



NEWMOA Thermal Remediation Workshop

51

Confirmation Soil Data: ISTD Project in Fractured Rock



NEWMOA Thermal Remediation Workshop

52

Summary, ISTD Project in Fractured Rock

- Rock heats more readily than overburden (less water and porosity).
- Crystalline rock cleans up readily.
- Total project cost including power: ~\$1.1M
- ~1.5M kWhr or 170 kWhr/cy.
- Unit cost including power: \$125/cy (power: ~\$12/cy)

NEWMOA Thermal Remediation Workshop

53

Summary

- ➡ • Steam-Enhanced Extraction (SEE)*
 - Electrical Resistance Heating (ERH)*
 - Electro-Thermal Dynamic Stripping Process (ET-DSP™)
- ➡ • In Situ Thermal Desorption (ISTD)*
 - Thermal Conduction Heating (TCH) + Vacuum Recovery
- ➡ • Combinations*: ISTD/SEE (ET-DSP™/SEE)
- Radio Frequency Heating

➡ Focus of Talk

*Offered by TerraTherm, Inc.

NEWMOA Thermal Remediation Workshop

54

Think Thermal When...

- ✓ You have a Source Zone, or Hot Spots
- ✓ Site is Heterogeneous and/or Low in Permeability
- ✓ Stringent Cleanup Levels Must be Achieved, Quickly (or you just need to remove a lot of mass)
- ✓ Excavation is Ruled Out or Impractical

Thermal is Especially Well Suited if:

- ✓ The Treatment Zone is Deep
- ✓ There's a Mixture of Contaminants
- ✓ The Site is Complex, and/or
- ✓ Long-Term O&M is Too Costly

5

5



NEWMOA Thermal Remediation Workshop

56

SUPPLEMENTAL MATERIAL - HOT SOIL SAMPLING

Griepke-Nielsen, S., et al, Remediation of Chlorinated and Recalcitrant
Compounds, Monterey, CA. 2012

NEWMOA Thermal Remediation Workshop

57

Soil Sampling during and after Thermal – How and When?

Steffen Griepke Nielsen, Pia Juul Jensen (formerly NIRAS A/S, Allerød, Denmark)

Gorm Heron (TerraTherm, Inc., Bakersfield, CA USA)

Jim Galligan and John LaChance (TerraTherm, Inc., Gardner, MA USA)

Peder Johansen (Capital Region of Denmark, Hillerød, Denmark)

Niels Ploug, Jesper Holm (Krüger, Gladsaxe, Denmark)



Key Questions

- How can one sample hot soil for reliable CVOCs concentration data?
- Will the thermally treated site experience rebound during the cooling period?
- Will it be necessary to repeat soil sampling once the site cools?

Sampling Equipment

- Intact core samples are needed to minimize vaporization of CVOCs during sampling
- Samples typically collected using a core barrel-type sampler equipped with stainless steel or Teflon sleeves
- Lengths and diameter of sample tools may vary from driller to driller



Equipment Decontamination

- Downhole equipment (augers, core barrels, drive rods, etc.) must be decontaminated prior to use
- Samples sleeves and end caps must be decontaminated if reused



Sample Collection

- The core barrel sampler and sample sleeve are assembled and advanced to the desired depth
- Samples are collected
- Full recovery not always possible



- Standard drilling equipment utilized



Sample Collection (Cont.)

- Once removed from the borehole, the core barrel is disassembled and the sample sleeve is removed
- The ends of the sample sleeve are immediately covered with Teflon tape and capped



Sample Collection (Cont.)

- Samples are placed into an ice bath for cooling containing drains to allow melt water to freely drain
- Once cooled to a temperature no higher than 10°C (50°F) the sample is ready to be containerized




Sample Collection (Cont.)



- Samples are sealed tightly in a plastic bag for shipment to the laboratory
- Laboratory will extrude the soil
- Alternatively, the cooled samples may be processed in the field
- Commercial systems like the En Core® sampler may also be utilized



Reerslev – PCE Source Zone with Plume






- Area: 1,300 m²
- Volume: 11,500 m³
- Days of operation: 169 days
- CVOC mass removed: 2,300 - 2,500 kg PCE (>97% of mass was PCE)

Reerslev (Capital Region of Denmark) - ISTD




Wellfield Layout






1st Event – Random Sampling



Sample Locations




1st Post-Treatment Soil Sampling Event

1st Post-Treatment

50 samples


Max: 0.057 mg/kg

Avg: 0.014 mg/kg




Post-Treatment Temperature Monitoring

- Temperatures monitored at 2 locations post-treatment
- Eight temperature monitoring rounds over a 22 month period





Sample Locations



2nd Post Treatment Soil Sampling Event

2nd Post Treatment
17 samples
Max: <0.01 mg/kg
Avg: <0.01 mg/kg





Lessons Learned

- How can one sample hot soil for reliable CVOCs concentration data?
Use proper hot soil sampling procedures.
- Will the thermally treated site experience rebound during the cooling period?
No, data collected in this study documents that no rebound occurs following cooling when the flux of contaminants back into the TTZ is limited.
- Will it be necessary to repeat soil sampling once the site cools?
No, data collected in this study documents that CVOC concentrations actually decreased after 22 months of cooling due to biological polishing at the Reerslev site.

References

Capital Region of Denmark. 2008a. MW Gjøes Vej, Reerslev. Forklassificerings-undersøgelse. NIRAS. May 2008 (in Danish).

Capital Region of Denmark. 2008b. MW Gjøes Vej, Reerslev. Supplerende Undersøgelser – Supplerende Forklassificering, Risikovurdering og Ventilationstest. NIRAS, August 2008 (in Danish).

Capital Region of Denmark. 2011. ISTD Entreprise, Entreprise 1, MW Gjøes Vej, Reerslev. Slutdokumentation. NIRAS. February 2011 (in Danish).

Capital Region of Denmark. 2012. ISTD Oprensning, MW Gjøes Vej, Reerslev. Jordprøvetagning i Afkølet Område. NIRAS. January 2012 (in Danish).

Gaberell, M., A. Gavaskar, E. Drescher, J. Sminchak, L. Cumming, W.-S. Yoon, and S. De Silva. 2002. "Soil Core Characterization Strategy at DNAPL Sites Subjected to Strong Thermal or Chemical Remediation." in: A.R. Gavaskar and A.S.C. Chen (Eds.), Remediation of Chlorinated and Recalcitrant Compounds—2002. Proceedings of the Third International Conference on Remediation of Chlorinated and Recalcitrant Compounds (Monterey, CA; May 2002). ISBN 1-57477-132-9. Battelle Press, Columbus, OH.

TerraTherm. 2011. Standard Operating Procedure. Hot Soil Sampling for Chlorinated Volatile Organic Compounds. TerraTherm. December 2009.